

CCT

COMMERCIAL CARPET TILE

TECHNICAL SPECIFICATIONS

STYLE

SEASIDE COLLECTION

SURF COLLECTION

CONSTRUCTION	TEXTURED PATTERNED LOOP	TEXTURED PATTERNED LOOP
FACE FIBER	TYPE 6 NYLON	TYPE 6 NYLON
DYE METHOD	SOLUTION	SOLUTION
GAUGE	5/64 (50.39 PER 10 CM)	5/64 (50.39 PER 10 CM)
STITCHES PER INCH	9.33 (36.73 PER 10 CM)	9.16 (36.06 PER 10 CM)
DENSITY	5,305 (197.12 KG/M ³)	5,538 (205.78 KG/M ³)
PILE THICKNESS	0.095" (2.41 MM)	0.091" (2.31 MM)
WEIGHT	14 OZ/YD ² (475 G/M ²)	14 OZ/YD ² (475 G/M ²)
BACKING TYPE	EXTREME PLUS	EXTREME PLUS
SIZES	18" X 36" (45.72 X 91.44 CM)	18" X 36" (45.72 X 91.44 CM)
COLORS	8	8
PATTERN REPEAT	N/A	N/A
PACKAGING	8 YD ² / 16 TILES	8 YD ² / 16 TILES
ADHESIVE	MAPEI ULTRABOND ECO 399	MAPEI ULTRABOND ECO 399
INSTALLATION METHOD	HORIZONTAL BRICK ASHLAR	HORIZONTAL BRICK ASHLAR, MONOLITHIC, VERTICAL ASHLAR

TESTING

DIMENSIONAL STABILITY (AACHEN TEST)	PASSES
ELECTROSTATIC PROPENSITY (AATCC 134)	LESS THAN 3.0 KV
FLOORING RADIANT PANEL (ASTM E648)	PASSES - CLASS 1; ≥ 0.45 WATTS/CM ²
SMOKE DENSITY (ASTM E662)	PASSES - ≤ 450
METHENAMINE PILL TEST (ASTM D2859)	PASSES
HEXAPOD (ASTM D5252) TARR	3.5 - SEVERE

ENVIRONMENTAL DATA

NSF/ANSI 140 CERTIFICATION	EXTREME PLUS MODULAR - GOLD
RECYCLED CONTENT	CONTAINS RECYCLED CONTENT
INDOOR AIR QUALITY	CRI GREEN LABEL PLUS CERTIFIED
PRODUCT DECLARATIONS	THIRD PARTY VERIFIED EPD, HPD
CARBON OFFSET	105% CRADLE TO GATE (A1 - A3), VISIT WEBSITE FOR MORE INFORMATION
LEED	MAY CONTRIBUTE TO LEED CREDITS: BUILDING PRODUCT DISCLOSURE & OPTIMIZATION - EPDS; BUILDING PRODUCT DISCLOSURE & OPTIMIZATION - SOURCING RAW MATERIALS; BUILDING PRODUCT DISCLOSURE & OPTIMIZATION - MATERIAL INGREDIENTS; IEQC2 - LOW EMITTING MATERIALS
MINDFUL MATERIALS MANUFACTURING	VISIT MINDFULMATERIALS.COM FOR CURRENT TRANSPARENCY INFORMATION CALHOUN, GA (USA) - ISO 14001 REGISTERED



WARRANTY

LIMITED LIFETIME WEAR & BACKING WARRANTY
LIMITED 15-YEAR STAIN RESISTANT WARRANTY
LIMITED 15-YEAR BLEACH RESISTANT WARRANTY



CONTRACT180.COM



CONTRACT180
MADE IN AMERICA